



DoP-Nr.: 110540

Declaration of Performance

According to annex III (EU) 305/2011 (construction product regulation)

1.	Unique identification code oft he product type	LAMOLTAN® B2-G56-60/55-3			
2.	Type, batch or serial number allowing identification oft he	See product label.			
	construction product as required pursuant to Article 11(4)				
3.	Intended use	Thermal insulation product for building			
		equipment and industrial installations			
		regarding DIN EN 14319-1			
4.	Name, registered trade name or registered trade mark and contact	LAMOLTAN®			
	address of the manufacturer as required pursuant to Article 11(5)	Lackfa Isolierstoff GmbH & Co. KG,			
		Industriestrasse 2, 25462 Rellingen			
5.	Where applicable, name and contact address of the authorized	Not relevant			
	representative whose mandate covers the tasks specified in Article				
	12(2)				
6.	System or systems of assessment and verification of constancy of	System 3			
	performance oft he construction product as set out in Annex V.				
7.	In case oft he declaration of performance concerning a	Notified testing laboratory No. 0751			
	construction product covered by a harmonized standard.	(FIW Munich) and No. 0800 (MFPA			
		Leipzig) performed the test reports on			
		the relevant declared characteristics			
		under system AVCP 3.			
8.	In case oft he declaration of performance concerning a	Not relevant			
	construction product for which a European Technical Assessment				
	has ben issued.				

9. Declared Performance

Significant property	Performance								Specification
Density [kg/m³]	≥ 55								DIN EN 845
Mean temperature [°C]	-30	-20	-10	±0	10	20	30	40	
Thermal conductivity									
Initial value [W/m·K]	0,021	0,022	0,023	0,023	0,025	0,026	0,027	0,029	EN 12667
Declared thermyl conductivity									EN 12667
λ_a [W/m·K]									
(Both sides diffusion-proof)	0,027	0,028	0,029	0,029	0,031	0,032	0,033	0,035	
Closed cell content CCC4 (≥ 90 %)							ISO 4590		
Reaction to fire RtF Class E							EN 13501-1		
Compressive strength CS(10\Y)200 (≥ 200 kPa)							EN 826		

For all other characteristics according to EN 14319-1: NPD (No Performance Determined)

10. The performance oft the product identifies in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Robin Endtner (Head of technical department)

Rellingen, 15.11.2017

(Signature)

LACKFA Isolierstoff GmbH & Co. KG, Industriestraße 2, D-25462 Rellingen, Germany Phone: +49 (0) 4101/39 16-0, Fax: +49 (0) 4101/39 16 16, E-Mail: info@lackfa.com